

**ATS 22 Soft Starters**

<b>PART No</b>	<b>DESCRIPTION</b>		<b>LIST PRICE</b>
ATS 22D17Q	7.5KW 400V	130x169x265	R 8,744.00
ATS 22D32Q	15KW 400V	130x169x265	R 9,556.00
ATS 22D47Q	22KW 400V	130x169x265	R 10,766.00
ATS 22D62Q	30KW 400V	145x207x295	R 11,342.00
ATS 22D75Q	37KW 400V	145x207x295	R 13,595.45
ATS 22D88Q	45KW 400V	145x207x295	R 14,865.00
ATS 22C11Q	55KW 400V	150x229x356	R 16,025.00
ATS 22C14Q	75KW 400V	150x229x356	R 18,632.00
ATS 22C17Q	90KW 400V	150x229x356	R 22,711.00
ATS 22C21Q	110KW 400V	206x299x425	R 26,445.00
ATS 22C25Q	132KW 400V	206x299x425	R 27,126.00
ATS 22C32Q	160KW 400V	206x299x425	R 33,505.00
ATS 22C41Q	220KW 400V	206x299x425	R 41,100.00
ATS 22C48Q	250KW 400V	304x340x455	R 51,477.00
ATS 22C59Q	315KW 400V	304x340x455	R 54,743.00

**all prices are List & exclude VAT**



**Connection to the motor's power supply line**

Motor power given in kW in accordance with standard IEC/EN 60947-4-2. 220 V control power supply

Motor				230...440 V - 50/60 Hz soft start - soft stop unit					
Power indicated on rating plate				Nominal current (I <sub>n</sub> ) (1)	Factory setting for current (I <sub>cL</sub> ) (1) (2)	Dissipated power at nominal current (4)	Dimensions (W x D x H)	Reference	Weight
230 V	400 V	440 V							
kW	kW	kW	A	A	W	mm			kg
4	7.5	7.5	14.0	17	39	130 x 169 x 265	ATS 22D17Q	7.000	
7.5	15	15	28.5	32	44	130 x 169 x 265	ATS 22D32Q	7.000	
11	22	22	42	47	48	130 x 169 x 265	ATS 22D47Q	7.000	
15	30	30	57	62	59	145 x 207 x 295	ATS 22D62Q	12.000	
18.5	37	37	69	75	63	145 x 207 x 295	ATS 22D75Q	12.000	
22	45	45	81	88	66	145 x 207 x 295	ATS 22D88Q	12.000	
30	55	55	100	110	73	150 x 229 x 356	ATS 22C11Q	18.000	
37	75	75	131	140	82	150 x 229 x 356	ATS 22C14Q	18.000	
45	90	90	162	170	91	150 x 229 x 356	ATS 22C17Q	18.000	
55	110	110	195	210	117	206 x 299 x 425	ATS 22C21Q	33.000	
75	132	132	233	250	129	206 x 299 x 425	ATS 22C25Q	33.000	
90	160	160	285	320	150	206 x 299 x 425	ATS 22C32Q	33.000	
110	220	220	388	410	177	206 x 299 x 425	ATS 22C41Q	33.000	
132	250	250	437	480	218	304 x 340 x 455	ATS 22C48Q	50.000	
160	315	355	560	590	251	304 x 340 x 455	ATS 22C59Q	50.000	